



Cool-Shot Ultra

Performance Enhancer for Air Conditioning and Refrigeration Systems



COOL-SHOT ULTRA is the High-Performance Additive that improves the performances of AC/R Systems with 6 mL (0.20 fl oz) of product only. **COOL-SHOT ULTRA** produces colder air, faster. It is an environmentally friendly product since it reduces CO₂ emissions, it extends the life of the AC/R System and reduces maintenance costs. It acts quickly and reduces the vibrations and the noise of the compressor.

COOL-SHOT ULTRA is composed of two Synthetic Catalysts and a Lubricating Agent which bring the AC/R Systems to a state of maximum efficiency. It eliminates the Oil Fouling phenomenon, namely oil residues attached to the inner walls of the refrigeration lines that hinder the exchange of heat, isolating the Refrigerant Gas and reducing the performance of the AC/R System.

COOL-SHOT ULTRA acts as a catalyst without causing chemical changes in the Lubricant, it allows the Refrigerant Gas to flow in direct contact with the surfaces of the pipes to achieve an excellent improvement in performances: **COOL-SHOT ULTRA** produces colder air, up to 5°C (9°F) less, increases of 73% the heat exchange of the Refrigeration Lines, reduces the energy consumption of the AC/R of at least 20%, increases of 54% the efficiency of the compressor lubricant prolonging its life by up to 50%, reduces the friction within the compressor thus reducing vibration and noise, it reduces maintenance costs by at least 20% and it is also fluorescent when exposed to any UV Light.

COOL-SHOT ULTRA is suitable for every kind of AC/R System, including the ones working with R134a and R1234yf.

Instructions for the use **COOL-SHOT ULTRA** in Vehicle A/C Systems:

Insert **COOL-SHOT ULTRA** in the A/C System of the Vehicle (dilution in the Compressor Lubricant = 1:125 by volume). Start the A/C System. During the normal activity **COOL-SHOT ULTRA** will bring back the A/C System to its maximum efficiency.

Instructions for the use of **COOL-SHOT ULTRA** in AC/R Systems:

Insert **COOL-SHOT ULTRA** in the AC/R System (dilution in the Compressor Lubricant = 1:125 by volume). Start the AC/R System. During the normal activity **COOL-SHOT ULTRA** will bring the AC/R System to its maximum efficiency.

COOL-SHOT ULTRA must be used by a professional, with the appropriate personal protective equipments.

